

PFL Sealer Stripper

PeterFell
SPECIALISTS IN COLOURED CONCRETE

PFL Sealer Stripper can be used to remove all PFL sealers from concrete surfaces.

Description:

PFL Sealer Stripper is a powerful solvent based stripper that dissolves all sealers in the PeterFell range. It is free of known carcinogens and does not contain caustic mineral acids typical of equivalent sealer strippers.

Precautions:

- While PFL Sealer Stripper will dissolve all PeterFell sealers, in most cases mechanical removal of the sealer is the recommended method for the removal of the sealer i.e. sanding or grinding. Mechanical removal of PeterFell sealers is a more efficient method than stripping, and avoids associated chemicals and cleanup required with use of PFL Sealer Stripper.
- For best results it is recommended that PeterFell sealers are removed by an experienced tradesperson or handyperson experienced in the stripping of floor sealers.
- PFL Sealer Stripper is EXTREMELY HAZARDOUS and should be used with extreme care - ensure all safety guidelines are read prior to use, and are strictly adhered to during application.
- PFL Sealer Stripper is HIGHLY FLAMMABLE (both liquid and vapours) and must be handled and stored with extreme care (see 'Safety and Handling').
- DO NOT dispose of PFL Sealer Stripper down drains or waterways.

Application:

Equipment: Broom/Brush or roller, commercial sander/buffer fitted with stripping pad, safety equipment (see 'Safety and Handling').

Preparation: Ensure surface is clean and free of contaminants.

Application:

- Apply PFL Sealer Stripper with broom/brush or roller thoroughly over floor surface.
 - Form coating of 2-4 mm over entire surface area
- DO NOT brush or roll back and forth excessively when applying as this will release solvents needed to dissolve sealer.
 - In hot weather a layer of plastic sheet placed over the top will slow release of the solvent.
- Leave stripper on the surface until sealer has softened sufficiently to allow removal
 - Dissolution of the sealer typically takes 20 to 60 minutes
 - This time will vary greatly depending on sealer type and number of coats, and the site conditions i.e. temperature, humidity etc.
- Once sealer has dissolved, remove the sealer from the floor by scrapping or scrubbing. It is recommended that loosened sealer is removed by commercial sander/buffer equipped with stripping pad according to manufacturers instructions.
 - Commercial sander/buffer are available from equipment hire stores or local hardware retailer.
 - Use appropriate stripping pad i.e. 3M Black Stripper pad 7200 or 3M Black High Productivity Stripper Pad 7300 or equivalent.
 - Ensure pad is suitable for removal of sealer from concrete surfaces.
- Remove ALL released sealer from concrete.
- Rinse surface thoroughly with clean water and dry.
 - Use a wet and dry vacuum cleaner to ensure all water removed from internal floors.

Coverage: Coverage is approximately 3-4 m² per litre.

- Coverage is dependent on application and site conditions.

Cleanup: Discard waste product in appropriate manner. DO NOT dispose PFL Sealer Stripper down drains or waterways. Consult local Waste Management Authority for appropriate disposal method.

Safety and Handling:

Hazard: PFL Sealer Stripper is a Class 3 hazard. It is harmful by inhalation, in contact with skin, or if swallowed. Irritating to respiratory system. PFL Sealer Stripper must be handled with extreme care. For full safety information refer to MSDS or contact Peter Fell Ltd.

UN Number: 1170 **DG Number:** 3b **Hazchem code:** 3

Safety: Wear suitable protective clothing, eye protection, protective gloves. In confined spaces or poorly ventilated areas use a respiratory mask with organic vapour cartridge.

Pack Sizes: 1, 2, 5, 10 and 20 L.

Storage: Store in cool, dry, well ventilated place in original container. Store out of reach of children. Store away from direct sunlight, oxidizing agents (e.g. nitrates, peroxides, hypochlorites), acids, anionic detergents (e.g. soap), and foodstuffs. Keep away from naked flames and other heat sources. Take precautions against static discharge. Ensure container is sealed when not in use, and checked regularly for leaks or spills. Do not allow vapours to collect in enclosed spaces. PFL Sealer Stripper can be stored for up to 12 months.

First Aid:

Swallowed: DO NOT induce vomiting. Give water or milk to drink. Obtain medical attention immediately. For emergency information contact the *National Poisons Centre (0800 764 766)*.

Eyes: Immediately flood with copious quantities of water, holding eye open if necessary, for at least 15 minutes. Seek urgent medical attention.

Skin: Remove contaminated clothing and shoes and wash skin thoroughly with excess water. If irritation occurs or persists, seek medical attention. Launder clothing and clean shoes before re-use.

Inhalation: Remove patient from exposure, keep warm and at rest. If there is respiratory distress, give oxygen and seek immediate medical attention.

Physical and Chemical Properties:

Appearance.....	clear viscous liquid
Odour.....	alcohol
Solubility (in water).....	partially soluble
pH.....	3.0
Flash Point (closed cap).....	>14°C
Specific Gravity.....	0.95 kg/L

Product Warranty

The information contained in this document is true and accurate to the best knowledge of Peter Fell Ltd. We cannot however anticipate all conditions under which this information and our products may be used. Peter Fell Ltd therefore accepts no responsibility and offers no warranty with respect to results obtained by the application of our products, their suitability, or for their safe use. Peter Fell Ltd offers our products for sale subject to, and 'The Customer' and all users are deemed to have accepted, our Terms and Condition of Trade. Peter Fell Ltd warrants our products to be free of manufacturing defects. If the product when purchased was defective and was within recommended storage life when used, Peter Fell Ltd will replace the defective product with new product without charge to the purchaser. Peter Fell Ltd makes NO OTHER WARRANTY, either expressed or implied, concerning our products.